## Felix A. Marino Co., Inc.

32 Corwin Street
Peabody, MA 01960
(978) 532-3838
sales@felixamarino.com



## MARIMIX<sup>TM</sup> | High Performance Bituminous Concrete

MARIMIX<sup>TM</sup> is a high performance bituminous concrete specifically designed for permanent pavement repairs. MARIMIX<sup>TM</sup> can be utilized cold, warm and/or hot. It handles easily even at cold winter temperatures. MARIMIX<sup>TM</sup> can be heated and reheated in pavement storage without damaging the properties of the material. MARIMIX<sup>TM</sup> is produced from 100% virgin materials and an enhanced modified binder, ensuring that it is completely recyclable even after placement.

## Why MARIMIXTM?

- Save over 30% from typical Cold Patch Method requiring removal and replacement
- 100% Virgin Material
- 1/2" Binder or 3/8" Top Gradations
- Utilize Cold, Warm or Hot
- Stockpile for the Winter Use all Year
- Use as an Admixture to HMA through thermal integration to ensure proper density and flexibility

Pavement depressions, potholes and/or utility cuts are prime candidates for MARIMIX<sup>TM</sup>. Just sweep the area to be repaired, tack coat the edges and install MARIMIX<sup>TM</sup> into the area. Compact in 2" layers, tack coat the seams and you have a permanent repair. No more digging out cold patch to make permanent repairs. Its enhanced design characteristics allow for a semi-permanent repair of utility excavations provided that it's properly installed and at sufficient thickness. MARIMIX<sup>TM</sup> installed stays pliable long enough to expedite the inevitable sub-base settlement of utility trenches while staying cohesive, allowing for less costly subsequent permanent restorations (such as conventional or thermal overlays) sooner than temporary

**MARIMIX**<sup>TM</sup> also is a superior patching material than hot mix asphalt for most potholes! All potholes need both water and traffic present to develop. Since all potholes have moisture, patching with hot mix asphalt attains a high cohesive patch but limits the patch to bond to the existing roadway. Oil and water do not mix. The modified binder contained in the **MARIMIX**<sup>TM</sup> product actually has an affinity to moisture resulting in an eventual chemical bond between patch and roadway. The long-term performance of **MARIMIX**<sup>TM</sup> as a patch material under high traffic is unmatched by any other material available.

**MARIVIX** can be purchased in bulk (ton quantities) and by 5-gallon pail. It can be stored at ambient temperatures. **MARIVIX** is available exclusively at Felix A. Marino Co., Inc.





